

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number
WO 2004/007199 A1

(51) International Patent Classification⁷: **B41C 1/045**

(74) Agents: NEILL, Alastair, William et al.; Appleyard Lees,
15 Clare Road, Halifax, HX1 2HY (GB).

(21) International Application Number:
PCT/GB2003/000744

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 20 February 2003 (20.02.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0216303.8 13 July 2002 (13.07.2002) GB

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): KEATING GRAVURE SYSTEMS UK LIMITED [GB/GB];
Unit 4, Bromfield Industrial Estate, Mold, Flintshire CH7 1HE (GB).

Published:


— with international search report

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): KEATING, Michael [GB/GB]; 25 Wycliffe Court, Hoole Lane, Chester CH2 3HA (GB).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVEMENTS IN AND RELATING TO GRAVURE PRINTING



(57) Abstract: The invention relates to a method of engraving a plurality of gravure cells in a surface, the method comprising the steps of: (a) mounting an engraving stylus comprising a stylus body inwardly tapering to the stylus tip, in an engraving head; (b) effecting penetration of the engraving stylus into the surface to a desired depth to produce a cell; (c) effecting partial withdrawal of the engraving stylus from the cell; (d) effecting relative movement between the stylus and the surface such that the partially withdrawn stylus effects engraving of a channel of shallower depth than the cell in the surface and having a channel width of at least 40% of the width of the previous cell engraved in the method; and (e) effecting further penetration of the engraving stylus into the surface to a desired depth, and effecting relative movement between the stylus and surface to produce a cell. The invention further relates to novel gravure engraving styli, comprising triangular prism, triangular prismoid or planar quadrilateral shaped tips.

WO 2004/007199 A1